

# 45W LED Slim Canopy Light





#### **Features**

- · Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V/AC347-480V.
- Die Cast aluminium cooling design, high quality and better cooling for LED Tj < 85℃. Excellent
- Optics design, greatly improve the light utilization and evenness.
- Motion sensor Control Available (Option).

## **Product Applications**

WISDOM LED Slim Canopy Light series can be widely used in outdoor lighting(Wet location), Excellent for Museums, Art Galleries, Parking Gragre, Buildings, The lawn, Industrial areas, Residential areas, Sidewalks, Schools and etc, and many more applications.







www.wisdom-ssl.com
















WISDOM OPTOELECTRONICS TECHNOLOGY CO., LIMITED Add: FLOOR 8, BUILDING B1 SUNSHINE INDUSTRIAL PARK HEZHOU XIXIANG BAOAN DISTRICT SHENZHEN, GUANGDONG, CHINA, 518126.

# **Specifications**


Unit:inch(mm)

#### **Structure Features**

- Shell materials: Aluminum & PC.
- Finish: Dark Bronze/White/Black
- Net weight: 2.47Kg (5.5 lbs)
- Product Size:255.5mm\*255.5mm\*83.7mm
- Carton Size:270mm\*270mm\*110mm









### **Technical Parameters**


WSD-CP45W27-XXK-Z[D,W,B,S]-*[Blank,M]								
Power	45W	Lighting Angle	159°					
Input Voltage	AC120-277V/AC347-480V	LED Brightness Decay	<5%/6000 hrs					
PF	>0.95	Working Life	>50000 hrs					
Driver Efficiency	>90%	Working Temperature	-30 - +45℃					
Luminous Flux	5991 Lm	Storage Temperature	-40 -+80°C					
Color Temperature	4000K/5000K	Protection Level	Wet Location/IP66					
CRI	Ra>70	Cable	Input Connect, 0.3m					
Optional dimming function	1-10Vdc	Eff	>130lm/w					

### **Photometry**

www.wisdom-ssl.com







Example:WSD-CP45W27-XXK-Z[D,W,B,S]-*[Blank,M]								
WSD	CP	45W	27	XXK	Z	*		
Conmpany	Product	Power	Voltage	Color Temp	Finish	Motion sensor		
	СР	45W(45W)	27	40K(4000K)	D (Dark Bronze)	M		
WISDOM	Slim Canopy		AC120-277V	50K(5000K)±500K	W (White)	Motion sensor		
			48		B (Black)			
			AC347-480V		S (Silvery)			